



15W-40 SYNTHETIC BLEND HEAVY-DUTY MOTOR OIL

Technical Data Sheet

Description

Majestic 15W-40 Heavy Duty Motor Oil is a high-performance multi-grade para-synthetic lubricant, designed for use in high speed, four-stroke diesel engines, carbureted, fuel injected, turbocharged and supercharged gasoline engines. Majestic 15W-40 Heavy Duty Motor Oil provides superior protection against wear, corrosion, oxidation and varnish. Our unique detergent additive prevents sludge or carbon deposits in extreme heat or pressure conditions. Majestic 15W-40 Heavy Duty Motor Oil is formulated with high viscosity-index Type II paraffinic and synthetic base stocks to provide superior anti-shear properties, enhances engine performance and extend oil life. Majestic 15W-40 Heavy Duty Motor Oil is designed to ease cold-starts and eliminate viscosity breakdown.

Applications

Majestic 15W-40 Heavy Duty Motor Oil is suitable for use in the following applications.

| | | |
|---------------------|----------------|--------------------|
| -API CK-4 | -API CJ-4 | -API CI-4 Plus |
| -API CH-4 | -API CF-4 | -API SN |
| -ACEA E9-12 | -Cummins 20086 | |
| -DDC 93K222 | -Volvo VDS-4.5 | -Caterpillar ECF-3 |
| -Mack EOS-4.5 | -Renault RLD-4 | -MB 228.31 |
| -MAN 3575 | -MTU2.1 | -DQC III-10-LA |
| -Ford WSS-M2C171-F1 | | |

Typical Characteristics

| SAE J300 VISCOSITY GRADE | 15W-40 |
|--------------------------|-----------------------------|
| Appearance | Amber, Bright, Free & Clear |
| Viscosity cSt @ 40°C | 103.4 |
| Viscosity cSt @ 100°C | 14.5 |
| Pour Point, °C | -30 |
| Flash Point, °C | 220 |
| Viscosity Index | 145 |

**The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.*

Attributes

- High performance multi-grade para-synthetic lubricant
- Designed for use in high speed, four-stroke diesel engines
- Designed for use in carbureted, fuel injected, turbocharged and supercharged gasoline engines
- Designed for superior protection against wear, corrosion, oxidation and varnish
- Unique detergent additive prevents sludge or carbon deposits in extreme heat or pressure conditions
- Formulated with high viscosity-index Type II paraffinic and synthetic base stocks
- Superior anti-shear properties
- Enhances engine performance
- Extends oil life
- Eases cold-starts
- Eliminates viscosity breakdown.

Product Codes

Majestic 15W-40 Heavy Duty Motor Oil is available in the below packaging. Please use the reference code when ordering.

- Bulk, MAJ-001
- 275 Gallon Tote, MAJ-001-T
- 55 Gallon Drum, MAJ-001-D
- 5 Gallon Pail, MAJ-001-P
- 3/2 Gallon Case, MAJ-001-2G
- 4/1 Gallon Case, MAJ-001-1G

Revised 03/01/2019