

SAE 80W-140 SYNTHETIC GEAR OIL API GL-5

Technical Data Sheet

<u>Description</u>

Majestic SAE 80W-140 Synthetic Gear Oil is formulated with synthetic base oils and a premium gear additive package to provide improved high-temperature thermal and oxidative stability in a wide range of operating conditions and advanced protection and lubricity in extreme pressure conditions. Majestic SAE 80W-140 Synthetic Gear Oil is highly shear stable while also resisting rust, oxidation, foaming, and varnish. This product is designed to exceed the year-around, all-weather performance viscosity requirements of SAE J306 as well as the rigorous performance requirements of API GL-5

<u>Applications</u>

Majestic SAE 80W-140 Synthetic Gear Oil is suitable for use in the following applications.

- -API GL-5
- -Mack GO-J Plus
- -API MT-1
- -SAE J2360
- -ZFTE-ML07A
- -MIL-L-2105D
- -MIL-PRF-2105E
- -Scania STO 1:0

Typical Properties

| SAE VISCOSITY | 80W-140 |
|-----------------------|---|
| Appearance | Light Yellow to Amber Transparent Liquid, Free |
| , pp = 33 | and Clear |
| Viscosity cSt @ 40°C | 188.9 |
| Viscosity cSt @ 100°C | 25 |
| Flash Point, °C | 225 |
| Viscosity Index | 165 |

^{*}The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

Attributes

- -Formulated with high viscosity-index, synthetic base oils and specialty performance additives
- -Formulated to provide improved high-temperature thermal and oxidative stability in a wide range of operating conditions
- -Provide advanced protection and lubricity in extreme pressure conditions
- -Highly shear stable while also resisting rust, oxidation, foaming, and varnish
- -Designed to exceed the year-around, all-weather performance viscosity requirements of SAE J306 as well as the rigorous

performance requirements of API GL-5

-Provided protection against the combination of thermal degradation, component wear, and oil seal deterioration

Product Codes

Majestic 80W-140 Gear Oil is available in the below packaging. Please use the reference code when ordering.

- Bulk, MAJ80W140B
- 275 Gallon Tote, MAJ80W140TG
- 55 Gallon Drum, MAJ80W14055G
- 5 Gallon Pail, MAJ80W1405G

Revised 03/01/2023