



SAE 80W-90 GEAR OIL API GL-5

Technical Data Sheet

Description

Majestic SAE 80W-90 Gear Oil is formulated with high viscosity-index, paraffinic base oils and specialty performance additives to produce a highly shear stable gear oil that resists rust, oxidation, foaming, and varnish. This product is designed for hypoids in automotive axles under high-speed and/or low-speed, high-torque conditions and provides advanced protection and lubricity in extreme pressure conditions.

Applications

Majestic SAE 80W-90 Gear Oil is suitable for use in the following applications.

-API GL-5

Typical Properties

SAE VISCOSITY GRADE	80W-90
Appearance	Amber Liquid, Free and Clear
API Performance Level	GL-5
Viscosity cSt @ 40°C	138.65
Viscosity cSt @ 100°C	15
Flash Point, °C	205
Viscosity Index	110

**The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.*

Attributes

- Formulated with high viscosity-index, paraffinic base oils and specialty performance additives
- Designed for hypoids in automotive axles under high-speed and/or low-speed, high-torque conditions
- Specialty anti-scuffing additives and friction modifiers
- Provides advanced protection and lubricity in extreme pressure conditions
- Highly shear stable
- Resists rust, oxidation, foaming, and varnish

Product Codes

Majestic 80W-90 Gear Oil is available in the below packaging. Please use the reference code when ordering.

- Bulk, MAJ80W90B
- 275 Gallon Tote, MAJ80W90TG
- 55 Gallon Drum, MAJ80W9055G
- 5 Gallon Pail, MAJ80W905G

Revised 03/01/2023